

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number  
**WO 2004/099586 A1**

(51) International Patent Classification<sup>7</sup>: **F02B 37/22,**  
37/013

(21) International Application Number:  
PCT/IB2003/001787

(22) International Filing Date: 8 May 2003 (08.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **HONEYWELL INTERNATIONAL INC.** [US/US]; 101 Columbia Road, Morristown, NJ 07962-1057 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KUMABE, Sergio,**  
Tetsuo [BR/BR]; Rua Francisco Martins Feitosa, 790,  
Mogi das Cruzes, Sao Paulo, CEP 08735-420 (BR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,  
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **CONTROL VALVE AND PARTS OF A TURBOCHARGER AND A TURBOCHARGER BOOSTING SYSTEM COMPRISING THE SAME**



(57) Abstract: A control valve comprises a movable flap (15) for a controlled closing or opening of a fluid passage (9, 3), wherein in the closed state the upstream side of said flap (15) extends in a plane being inclined to the extension direction of the passage (9, 3). Such a control valve is used in a turbine housing or compressor housing of a turbocharger.

WO 2004/099586 A1